

HM1212 & HW1212

The HW1212 & HM1212 is a heavy-duty horizontal saw built to provide decades of precise cutting. This reliable half-ton saw features a hydraulic feed system for controlled feed rate and a frame that quickly swivels 60° in either direction for accurate cutting for up to 12" material.

With a quick clamp that can be moved to either side of the 13" x 26.5" table, material can be fed from either direction, allowing more versatility.

The built-in coolant system on the HW1212 version has side splash panels, an 8 gallon coolant reservoir, and 3.5 gpm pump. This HW1212 built-in coolant system provides you a cleaner system that provides extended life of the blade.



Feed System	Hydraulic cylinder for controlled feeds
Blade Travel	12"
Cutting Capacity at 90°	Round: 12" - Rectangle: 12" x 10" - Square: 10"
Cutting Capacity at 45°	Round: 9" Square: 9"
Cutting Capacity at 60°	Round: 6" Square: 6"
Miter Cut Angle Range	0° - 60° (Saw Head Swivels 60° In Both Directions)
Bevel Cut Angle Range	N/A
Capacity Under Guides	12"
Blade Size (Ships With Saw)	1" Width x 11' 8" Length x .035 Thick (bi-metal)
Blade Size (Accepted Widths)	1"
Blade Speeds	70/140/270 sfpm
Table	Precision Ground Steel Table: 13" x 26.5"
Table Height	30" From Floor (No Casters)
Motor	1 HP, 110/220 single-phase
Saw Dimensions	26" Width x 50-1/2" Height x 73" Length
Shipping Dimensions	41" Width x 56.5" Height x 96" Length
Shipping Weight	1,000 lbs. F.O.B. Cleveland, Ohio

HM1212 Price: \$6,705

HW1212 Price: \$7,145

HM1212 & HW1212

Fast accurate cut on materials up to 12" thick

Saw easily swivels up to 60° in either direction, allowing for precise angled cuts

The weighted/hydraulic feed coupled with the automatic stop switch allows for large production and unsupervised cuts

Built-in coolant system enables faster cuts and extends the life of the saw blades (HW1212)

